

18 Gauge Fusion Tool Comparison Chart



| | SENCO FUSION | PASLODE | FUSION BENEFITS |
|----------------------------------|---|------------------------------|--|
| Nail Diameter | 18 ga. Straight | 18 ga. Straight | |
| Warranty | 2 Years - Tool; 1 Year - Battery | 90-Day Parts; 1 Year Limited | Increased User Confidence |
| Fuel Cells Required | NO - Never! | YES | Save Up to \$300/Year |
| Cleaning Required | NO | YES | Save Up to \$50/Year; Less Downtime |
| Instant Drive After Trigger Pull | YES | NO | Pneumatic "Feel"; No Gas = No "Ramp Up" |
| Firing Modes | Sequential, Bump Fire or Off | Sequential Only | Single or Multi-Shot Operation |
| Depth of Drive Adjustment | Mechanical with Guide | Mechanical | Precise Depth Control; Countersink or Flush |
| Battery | 18V Li-ion | 6V Ni-Cd | No Partial Drives |
| Battery Charge Indicator | YES | NO | Easy Notification of Charge Level |
| Battery Charge Time | 80% in 15 Min.; 100% in 45 Min. | 2 Hours | Less Downtime. More Productivity |
| Belt Hook | YES - Reversible/Adjustable | YES - Reversible Only | Accommodates Various Tool Belt Styles & Sizes |
| Work Light | YES | NO | Accurate Fastener Placement |
| Magazine Capacity | 110 | 100 | More Fasteners = Less Loading |
| Magazine Material | Composite | Composite | |
| Weight (lbs.) | 6.0 | 4.9 | |
| Tool Height | 13" | 11.5" | |
| Tool Width | 3" | 3.5" | Improved Line of Sight & Fastener Placement |